







SX Series external stern thrusters



The efficient stern thruster option for boats with twin stern drives!

Side-Power now offers a complete external stern thuster assembly, specially designed for installation on boats with twin stern drives. It utilizes special cowls to enable good performance by diverting the waterflow past the stern drive legs, which normally blocks the waterflow and the thrust.

The units come pre-assembled, wired and sealed in the waterproof box, and only require a small hole into the boat's transom to attach the power and control cables. The cable connection points are fully sealed, so that it is Ignition Protected and can be installed in petrol powered boats.

This stern thruster option can also be the best choice for boats without stern drives, if the inside configuration of the boat's stern makes a standard thruster installation impractical.

Also available in PRO versions with DC speed control.





SX Series thrusters SX 80/185 T SX 100/185 T

| Item Code 24V Item Code I2V PRO* Item Code 24V PRO* | SX80/185T-24V SXP80/185T-12V SXP80/185T-24V | SX100/185T-24V SXP100/185T-12V SXP100/185T-24V |
|---|---|--|
| Item Code I2V | SX80/185T-12V | SX100/185T-12V |
| Rec. CCA (DIN** 12/24V) | 550/300 | 750/400 |
| Weight (kg • lbs) | 52 • 115 | 57 • 125 |
| For DC system (V) | 12/24 | 12/24 |
| Power at 10.5V/21V* (kw • Hp) | 4.4 • 6 | 6.3 • 8.4 |
| Propulsion system | Twin | Twin |
| Tunnel I.D. (mm • in) | 185 • 7.3" | 185 • 7.3" |
| Typical boat size (ft • m) | 35' - 48' • 10 - 15 | 35' - 55' • 12 - 17 |
| Thrust at 12V/24V* (kg · lbs) | 96 • 212 | 116 • 256 |
| Thrust at 10.5V/21V* (kg · lbs) | 80 • 176 | 100 • 220 |

